

**MSDS - Material Safety Data Sheet****Product Name: LIQUID WRENCH MULTI-USE LUBRICATING OIL**

MSDS No.: L234

**I. Basic Information:****Manufacturer:** RADIATOR SPECIALTY COMPANY**Address:** 600 RADIATOR ROAD**City, ST Zip:** INDIAN TRAIL, NC 28079**Country:****Contact:** Robert Geer**Information Telephone Number:** 704-684--181 1**Emergency Contact:** Rocky Mountain Poison Control Center**Emergency Telephone Number:** 303-623-5716**Emergency Restrictions:****Product Name:** LIQUID WRENCH MULTI-USE LUBRICATING OIL**MSDS No.:** L234**Issue Date:** 08/07/2009**Supersedes Date:** 06/04/2009**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Combustible. Harmful or fatal if swallowed. Eye and skin irritant.

**OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Health Effects****Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

See signs and symptoms below

**Signs and Symptoms:**

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat &amp; stomach.

**Medical Conditions Generally Aggravated by Exposure:**

None Known

**Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Potential Environmental Effects**

Not Available

**III. Composition/Information on Ingredients:**

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
Aliphatic Hydrocarbon - Non Exempt.	8052-41-3	30.0 - 60.0	
Corrosion Inhibitor	Proprietary	1.0 - 5.0	
Ethylbenzene	100-41-4	0.1 - 1.0	
Mesitylene	108-67-8	1.0 - 5.0	
Naphthenic Petroleum Distillate	64742-52-5	30.0 - 60.0	
Tripropylene Glycol Monomethyl Ether	25498-49-1	1.0 - 5.0	
Xylene (mixed isomers)	1330-20-7	1.0 - 5.0	

## MSDS - Material Safety Data Sheet

**Product Name: LIQUID WRENCH MULTI-USE LUBRICATING OIL**

MSDS No.: L234

### IV. First Aid Measures:

#### **Emergency and First Aid Procedures:**

Eye Contact: Flush eyes with clean water for 20 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash skin with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Remove and isolate contaminated clothing. Launder contaminated clothing before reuse.

Inhalation: Move victim to fresh air. If breathing becomes difficult, administer oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

#### **Note to Physicians:**

N/E

### V. Fire Fighting Measures:

#### **Suitable Extinguishing Media:**

Water Fog, Foam, Carbon Dioxide, Dry Chemical

#### **Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread.

#### **Products of Combustion:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

#### **Protection of Firefighters:**

Wear self-contained positive pressure breathing apparatus and protective clothes.

### VI. Accidental Release Measures:

#### **Personal Precautions:**

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

#### **Environmental Precautions:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

#### **Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

#### **Methods for Cleanup:**

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

#### **Other Information:**

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

### VII. Handling and Storage:

#### **Handling Precautions:**

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

#### **Storage Precautions:**

Store in cool, well ventilated area below 120°F away from heat, fire, sparks or flame.

### VIII. Exposure Controls/Personal Protection:

**MSDS - Material Safety Data Sheet****Product Name: LIQUID WRENCH MULTI-USE LUBRICATING OIL**

MSDS No.: L234

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Aliphatic Hydrocarbon - Non Exempt.	100 ppm	100 ppm	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available
Mesitylene	N/A	N/A	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available
Tripropylene Glycol Monomethyl Ether	N/E	N/E	Not Available
Corrosion Inhibitor	N/E	N/E	Not Available
Ethylbenzene	100 ppm	100 ppm	Not Available

**Engineering Controls:**

See above Section for applicable exposure limits. If TLV is exceeded, wear NIOSH approved respirator.

**Personal Protective Equipment:**

Use with adequate ventilation. For prolonged exposure wear protective safety glasses, gloves, and apron.

**IX. Physical and Chemical Properties:****Boiling Point:** 320 F**Boiling Range:** N/D**Solubility In Water:** Insoluble**Flash Point:** 132F**Odor Threshold:** N/D**Vapor Density (AIR = 1):** N/D**pH Range:** N/A**Decomposition Temp:** N/D**Lower Explosive Limit:** 0.7%**Specific Gravity (H2O = 1):** 0.81**Other Information:** VOC Content: 47.6% (Wt.)**Melting Point:** N/A**Freezing Point:** N/D**Evaporation Rate (Butyl Acetate = 1):** N/A**Flash Point Method:** TCC**Appearance and Odor:** Clear light yellow with sweet vanilla odor**Vapor Pressure (mm Hg.):** N/D**Partition Coefficient:** N/D**Auto-Ignition Temp:** N/D**Upper Explosive Limit:** 5%**X. Stability and Reactivity:****Stability:**

Product is stable

**Conditions to Avoid:**

Avoid heat, sparks, and flames. Avoid incompatible materials.

**Incompatible Materials:**

Avoid contact with strong oxidizers

**Hazardous Decomposition Products:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

**Possibility of Hazardous Reactions:**

Will not occur

**XI. Toxicological Information:**

N/D

**MSDS - Material Safety Data Sheet****Product Name: LIQUID WRENCH MULTI-USE LUBRICATING OIL**

MSDS No.: L234

**XII. Ecological Information:**

N/D

**XIII. Disposal Considerations:**

DISPOSAL: This container may be recycled in a recycling centers when empty. Before offering for recycling, empty the can or bottle by using the product according to the label. If recycling is not available, wrap the empty container and discard in the trash. Do not dump into sewers, on the ground, or into any body of water. Dispose of unused product in accordance with all local, state government and federal laws and regulations

**XIV. Transport Information:****Shipping Name:** Consumer Commodity**DOT Hazard Class:** Not Available**DOT Subsidiary Hazard Class:** Not Available**UN/NA#:** Not Available**Packing Group:** Not Available**Transportation Information:**

DOT Hazard Class: Not Regulated

Shipping Name: Not Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

**XV. Regulatory Information:**

SARA Reportable Chemicals.

Aliphatic Hydrocarbon (8052-41-3)

1,2,4-Trimethylbenzene (95-63-6)

Xylene (1330-20-7)

Ethylbenzene (100-41-4)

USA TSCA: All components of this material are either exempt or listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

State RTK Chemicals

Aliphatic Hydrocarbon 8052-41-3

1,2,4-Trimethylbenzene 95-63-6

1,3,5-Trimethylbenzene 108-67-8

Xylene 1330-20-7

Ethylbenzene 100-41-4

**XVI. Other Information:****Chemical State:**  Liquid  Gas  Solid**Chemical Type:**  Pure  Mixture**Hazard Category:**
 Acute  Chronic  Fire  
 Pressure  Reactive
**Additional Manufacturer Warnings:**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established

N/D: Not Determined

N/A: Not Applicable

N/AV: Not Available

**Additional Product Information:**

2	Health
2	Flammability
0	Physical Hazard
C	Pers. Protection

## ***MSDS - Material Safety Data Sheet***

***Product Name: LIQUID WRENCH MULTI-USE LUBRICATING OIL***

***MSDS No.: L234***

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.