

**MSDS - Material Safety Data Sheet****Product Name: HEAVY DUTY SPRAY LUBRICANT WITH PTFE****MSDS No.: L508****I. Basic Information:****Manufacturer:** RADIATOR SPECIALTY COMPANY**Address:** 600 RADIATOR ROAD**City, ST Zip:** INDIAN TRAIL, NC 28079**Country:****Contact:** Robert Geer**Information Telephone Number:** 704-684-1811**Emergency Contact:** Rocky Mountain Poison Control Center**Emergency Telephone Number:** 303-623-5716**Emergency Restrictions:****Product Name:** HEAVY DUTY SPRAY LUBRICANT WITH PTFE**MSDS No.:** L508**Issue Date:** 03/04/2008**Supersedes Date:** 05/16/2003**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Extremely Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

**OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Health Effects****Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

See Signs and Symptoms below

**Signs and Symptoms:**

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat &amp; stomach.

**Medical Conditions Generally Aggravated by Exposure:**

N/D

**Other Health Warnings:**

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

**Potential Environmental Effects**

Not Available

**III. Composition/Information on Ingredients:**

Chemical Name	CAS No.	% Range	Trade Secret
Butane	106-97-8	5.0-10.0	
Isobutane	75-28-5	7.0-13.0	
Naphthenic Petroleum Distillate	64742-52-5	40.0 - 70.0	
Propane	74-98-6	7.0-13.0	

**IV. First Aid Measures:****Emergency and First Aid Procedures:**

# *MSDS - Material Safety Data Sheet*

## *Product Name: HEAVY DUTY SPRAY LUBRICANT WITH PTFE*

**MSDS No.:** L508

**Eye Contact:** Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

**Skin Contact:** Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

**Inhalation:** Remove to fresh air. If breathing becomes difficult give oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

**Ingestion:** DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

**Note to Physicians:**

N/D

### ***V. Fire Fighting Measures:***

**Suitable Extinguishing Media:**

Water Fog, Foam, Carbon Dioxide, Dry Chemical

**Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread.

**Products of Combustion:**

Avoid contact with strong oxidizers

**Protection of Firefighters:**

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

### ***VI. Accidental Release Measures:***

**Personal Precautions:**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**Environmental Precautions:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

**Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

**Methods for Cleanup:**

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

**Other Information:**

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occurred.

### ***VII. Handling and Storage:***

**Handling Precautions:**

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Do not store at temperatures above 120°F, may cause container to vent, rupture, or burst.

**Storage Precautions:**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS! Danger: Flammable.

### ***VIII. Exposure Controls/Personal Protection:***

<b>Chemical Name</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Limits</b>
Butane	N/E	800 ppm	Not Available
Propane	N/E	1000 ppm	Not Available
Isobutane	1000 ppm	1000 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available

# MSDS - Material Safety Data Sheet

## Product Name: HEAVY DUTY SPRAY LUBRICANT WITH PTFE

MSDS No.: L508

### Engineering Controls:

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

### Personal Protective Equipment:

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

## IX. Physical and Chemical Properties:

**Boiling Point:** >300° F

**Boiling Range:** Not Available

**Solubility In Water:** Insoluble

**Flash Point:** < 20°F

**Odor Threshold:** Not Available

**Vapor Density (AIR = 1):** N/A

**pH Range:** Not Available

**Decomposition Temp:** Not Available

**Lower Explosive Limit:** 0.7%

**Specific Gravity (H2O = 1):** 0.90

**Other Information:** N/D

**Melting Point:** N/A

**Freezing Point:** Not Available

**Evaporation Rate (Butyl Acetate = 1):** N/A

**Flash Point Method:** Calculated

**Appearance and Odor:** Yellow amber oily liquid with mild hydrocarbon odor.

**Vapor Pressure (mm Hg.):** N/A

**Partition Coefficient:** Not Available

**Auto-Ignition Temp:** Not Available

**Upper Explosive Limit:** 5%

## X. Stability and Reactivity:

### Stability:

Stable

### Conditions to Avoid:

See Incompatible Materials below

### Incompatible Materials:

Avoid contact with strong oxidizers

### Hazardous Decomposition Products:

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

### Possibility of Hazardous Reactions:

Will not occur

## XI. Toxicological Information:

N/D

## XII. Ecological Information:

N/D

## XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

## XIV. Transport Information:

**Shipping Name:** Not Available

# MSDS - Material Safety Data Sheet

**Product Name:** *HEAVY DUTY SPRAY LUBRICANT WITH PTFE*

**MSDS No.:** L508

**DOT Hazard Class:** Not Available

**DOT Subsidiary Hazard Class:** Not Available

**UN/NA#:** Not Available

**Packing Group:** Not Available

**Transportation Information:**

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

UN Number: UN1959

Shipping Name: Aerosols

Class: 2.1

International:

ICAO/IATA

UN Number: UN1950

Shipping Name: Aerosols

Class: 2.1

IMDG

UN Number: UN1950

Shipping Name: Aerosols

Class: 2.1

EmS: F-D, S-U

**XV. Regulatory Information:**

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are listed on the US TSCA Inventory.

**XVI. Other Information:**

**Chemical State:**  Liquid  Gas  Solid

**Chemical Type:**  Pure  Mixture


**Hazard Category:**  
 Acute  Chronic  Fire  Pressure  Reactive



**Additional Manufacturer Warnings:**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established  
 N/D: Not Determined  
 N/A: Not Applicable  
 N/AV: Not Available



**Additional Product Information:**

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.