

# PRODUCT INFORMATION



**ENVIRONMENTALLY RESPONSIBLE  
SILICONE  
SPRAY LUBRICANT**

**CODE:** AM914

**PAGE:** 1 of 1

**DATE:** 1/22/2008

**FUNCTION & APPLICATION:** Stops squeaking and sticking, prevents rust and corrosion, lubricates doors, locks, drawers, and windows. It is also useful for other home applications as well as for automotive, shop, and industrial use, and for sports and athletic equipment.

**NOTE:** Not suitable for equipment or surfaces, which do not permit quick evaporation to the open air. Some surfaces, such as treadmills, require faster evaporation than this product affords. Not recommended for mold release applications.

**ENVIRONMENTALLY RESPONSIBLE:** This product has been formulated to reduce or eliminate adverse environmental characteristics. It is Non-Corrosive, and contains No Ozone Depleters and No Chlorinated Solvents.

**USE DIRECTIONS:** Shake container well before using. Spray surfaces lightly. Take care to avoid spraying on floors or stairways. Work lubricant in by moving parts and surfaces back and forth.

**PRECAUTIONS:** Contains (CAS#) Aliphatic Solvent Naphtha (64742-88-7), Propane (CAS# 74-98-6), Butane (106-97-8), and Dimethyl polysiloxane (CAS# 63148-98-6). Contents under pressure. Inhaling concentrated vapors, intentionally or otherwise, can be harmful or fatal. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. If inhaled, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention. In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If irritation persists, get prompt medical attention.

**STORAGE & HANDLING:** Store in a cool, dry, well ventilated area below 120°F. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** This product is packed in 13-ounce aerosol container.

## **Radiator Specialty Company**

**600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK**

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.