

# PRODUCT INFORMATION



## BATTERY TERMINAL PROTECTOR (AEROSOL)

**CODE:** BTP4

**PAGE:** 1 of 1

**DATE:** 01/21/2008

**FUNCTION AND APPLICATION:** Solder Seal/Gunk ® Battery Terminal Protector provides a special protective coating which when sprayed on the battery terminals, connectors, battery tray, and holder bolts and bracket hardware.

**OUTSTANDING PROPERTIES:** Prevents battery acid corrosion on the terminals and battery hardware. Ensures maximum starting current. Ensures that maximum charging current from the generator reaches the battery. Reduces battery maintenance when used with Solder Seal/Gunk ® Battery Terminal Cleaner to prevent acid corrosion, which can shorten the life of the battery, connectors, holder, bolts and bracket.

**USE DIRECTIONS:** For best results use Solder Seal/Gunk ® Battery Terminal Cleaner first. Shake can well before using container. Spray battery terminals, connectors, holder, and bracket and bolts. Apply every six months for preventative maintenance.

**PRECAUTIONS:** Contains (CAS#) petroleum distillates (64742-47-8), propane (74-98-6), and butane (106-97-8), and lithium grease. Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure. **FIRST AID:** For eye contact: flush with clean water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact: wash with soap and water. For inhalation: move to fresh air. For ingestion Drink water or milk. Do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. Consult Material Safety Data Sheet for additional information.

**HANDLING & STORAGE:** Use with adequate ventilation. Inhaling concentrated vapors can be harmful or fatal. Do not use or store near fire, sparks, or flames. Keep metal can from contact with electrical connections such as battery terminals. Such contact could result in can burn-through and flash fire resulting in serious bodily injury. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause container to burst, rupture, or vent violently. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** 4.5-weight oz aerosol container.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.