

# PRODUCT INFORMATION



## 10-MINUTE FLUSH

CODE: C1412

PAGE: 1 of 1

DATE: January 2008

**FUNCTION AND APPLICATION:** Flushes rust, scale and deposits from the cooling system when changing coolant or as a periodic cleaner.

**OUTSTANDING PROPERTIES:** Cleans grease, oil, scum and deposits from the cooling system in 10 minutes. Does not require a neutralizer.

**USE DIRECTIONS:** Allow engine and cooling system to cool. Drain cooling system. **NOTE:** Used anti-freeze/coolant and radiator fluids may be considered hazardous in some areas. Dispose of in sanitary sewer system where permitted. Never pour onto ground or into storm or septic sewer systems. (See DISPOSAL, below) Pour entire contents of container into radiator and refill with water. Run engine 10 minutes and drain system. Use caution when removing radiator cap while system is hot. Flush until water is clean. Refill cooling system with the appropriate coolant and water blend.

**PRODUCT LIMITATIONS:** Mild cleaner. Will not flush out severe accumulations of deposits and rust. Adequate for most applications. For severely clogged systems, use SOLDER SEAL® GUNK® Super Heavy Duty Radiator Cleaner (C22-32) or consult a professional radiator repair shop.

**PRECAUTIONS:** Contains 2-Butoxy-1-Ethanol (CAS# 111-76-2). May cause eye burns. Prolonged skin exposure may cause burns or organic damage. Harmful or fatal if swallowed. KEEP AWAY FROM CHILDREN. **FIRST AID:** If eye contacted, flush with water for at least 15 minutes and get prompt medical attention. If skin is contacted, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If swallowed, give two glasses of water. DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

**STORAGE & HANDLING:** Store away from oxidizing agents and strong acids.

**DISPOSAL:** Use and dispose of product, container, residue and used Anti-freeze/coolant and Radiator Fluids in accordance with all local, state and federal laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto ground or into storm sewer systems.

**CONTAINER DESCRIPTION:** Packed 11 fluid ounces in a plastic bottle.

## Radiator Specialty Company

600 Radiator Road, Indian Trail, North Carolina 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.