

# PRODUCT INFORMATION



## CONCENTRATED CLEANER DEGREASER

CODE: CL32, CL128  
CL49

PAGE: 1 of 1

DATE: July 2009

**FUNCTION AND APPLICATION:** Solder Seal/Gunk Concentrated Cleaner Degreaser was developed and formulated for Automotive, Home, and Industrial use. Concentrated Cleaner Degreaser is a powerful, fast acting degreaser that removes grease, oil, wax, tar, and dirt. Use it full strength on cold engines, tires, concrete floors, greasy shop clothing, vinyl siding, tile flooring, ovens, appliances, porcelain, and stainless steel.

**OUTSTANDING PROPERTIES:** Formulated to be fast acting. Spray it on, wipe or hose it off. One container goes very far with low cost.

**USE DIRECTIONS:** Wear proper eye protection and gloves when using this product. Spray Cleaner Degreaser onto item, let stand for a few minutes. Wipe away with a wet sponge or cloth. Extremely severe grime may require a second application. Rinse thoroughly with water. To limit over spray, do not use on windy days

**PRODUCT LIMITATIONS:** Will not prevent rubber cracks due to age and ozone attack. Avoid contact with aluminum or magnesium wheels, painted surfaces, glass and non-rubber surfaces. If splashed on these surfaces, rinse off over spray promptly to prevent damage.

**PRECAUTIONS:** Contains (CAS#) Tripropylene Glycol Monomethyl Ether (25498-49-1), Sodium Silicates (1344-09-8), Sodium Tripoly Phosphate (7758-29-4) and Surfactant (1643-20-5). Eye and Skin Irritant. Harmful if swallowed. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For inhalation, move to fresh air. If breathing becomes difficult, get prompt medical attention.

**STORAGE & HANDLING:** Store in a cool place below 120°F away from oxidizing agents. Keep from freezing. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** Packaged in 32 fluid-ounce bottle, 1-gallon and 55 gallon container.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.