

# PRODUCT INFORMATION



## ENGINE BRITE® HEAVY-DUTY ENGINE DEGREASER

**CODE:** EB1

**PAGE:** 1 of 1

**DATE:** 1/22/2008

**FUNCTION AND APPLICATION:** Removes grease and grime from auto, power mower, marine and tractor engines, metals, concrete and tires, industrial equipment where water is permitted.

**OUTSTANDING PROPERTIES:** Requires no tools or special skills. Inexpensive way to clean equipment. Emulsifies oil and greasy surfaces clean before your eyes.

**USE DIRECTIONS:** 1) Engine must be off and cool. 2) Cover distributor, electronic components, carburetor, and air intake systems. Care must be taken with all underhood wiring and electronic sensors or components. Minimize rinse water that can cause performance problems. Exposed electrical conductors (cracked or frayed wires or EC unit) can short circuit. 3) Spray generously on dry engine. Wipe any overspray from exterior body surfaces with a wet cloth at once to avoid dewaxing or streaking paint. 4) Allow ENGINE BRITE-ENGINE CLEANER to soak for 10 to 15 minutes (brush unusually heavy deposits). 5) Rinse with a fine stream of water from top down.

**SAFEGUARD OUR ENVIRONMENT...USE THE MINIMUM AMOUNT OF WATER NECESSARY TO REMOVE GRIME AND DIRT** and see Disposal Statement below.

6) When complete, remove all covers and replace any removed parts. Start engine immediately and idle for 15 minutes to assure complete drying.

**NOTE:** Never start your engine after you have applied ENGINE BRITE-ENGINE CLEANER until entire engine is thoroughly rinsed.

**PRODUCT LIMITATIONS:** Rinse overspray from exterior body surfaces immediately to avoid dewaxing or streaking paint. Avoid use of Engine Brite® on rubber tile, asphalt,

black top or other surfaces affected by petroleum solvents.

**PRECAUTIONS:** Contains (CAS#) Ethoxylated Nonyl Phenol (9016-45-9, Aliphatic Petroleum Distillate (68476-34-6), Aromatic Petroleum Distillate (64742-94-5), 2-Butoxy, Ethanol (111-76-2), Sodium Petroleum Sulfonate (68608-26-4), and Carbon Dioxide Propellant (124-38-9). Flammable. **Harmful or fatal if swallowed.** If ingested, do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact, flush with water for at least 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash with soap and water. Inhalation: If breathing becomes difficult, get prompt medical attention.

**STORAGE & HANDLING:** Use in a well-ventilated area. Store in a cool place, under 120°F. Keep away from heat, sparks or flame. Do not puncture or incinerate container. **KEEP AWAY FROM CHILDREN AND ANIMALS.**

**DISPOSAL:** SAFEGUARD OUR ENVIRONMENT...Disposal of rinse water in water courses, sewers, or on the ground may be prohibited. Such disposal is prohibited in California. Proper disposal includes collecting and evaporating the rinse water and recycling or disposal of any residue in accordance with state and local law.

**CONTAINER DESCRIPTION:** This product is available in 15 oz aerosol, quart spout can, 5 gallon spout pail and 30 or 54 gallon steel drum.

### Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

**NOTICE:** While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.