

PRODUCT INFORMATION



SUPER OIL

CODE: L1004

PAGE: 1 of 1

DATE: July 2008

FUNCTION AND APPLICATION: A light grade non-detergent machine oil (5 to 10 wt-SAE Grade) that lubricates and protects metal parts against wear, tarnish, rust and corrosion.

OUTSTANDING PROPERTIES: Meets Government Spec. MIL-L-644B for Lubricating Oil, General Purpose, Preservative (Water-Displacing, Low Temperature) oil. This product has a high flash point (over 275°F); will not corrode or discolor sensitive metals such as copper, aluminum, magnesium. Leaves no gumminess or tackiness; prevents rusting by displacing water and forming a preservative film on metallic surfaces. Films of SOLDER SEAL® GUNK® SUPER OIL® are readily removable with naphtha, lighter fluid and other household solvents.

USE DIRECTIONS: Apply as needed to metal surfaces and mechanisms. May be spread on surfaces with cotton swabs or cloth. Suggested for use on electrical motors, generators, industrial machines, refrigerators, vacuum cleaners, locks, hinges, casters, bicycles, typewriters, clocks, sewing machines, firearms and sporting equipment.

PRODUCT LIMITATIONS: Will not provide a long-lasting protective film with one application. Repeat applications will be necessary. Not for use on food equipment. Will not provide adequate protection for heavy duty machinery in continuous operation.

PRECAUTIONS: Contains White Mineral Oil (CAS# 8042-47-5) Harmful or Fatal if Swallowed. Eye and Skin Irritant. Mist may be harmful. **FIRST AID:** If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact flush with water for at least 15 minutes and get prompt medical attention. For skin contact wash thoroughly with soap and water. If irritation persists, get prompt medical attention. In case of inhalation, remove to fresh air.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C away from oxidizing agents, acids and ignition sources. **CAUTION:** Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. If bulk handling, wear chemical goggles and solvent-proof gloves and apron. Do not breathe vapors, gas or mist. Use only in well ventilated area. Open doors and windows to prevent build up. Keep away from children and animals. See M. S. D. S. for more information.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: Packaged in 4 fl oz can with squirt spout in bulk and carded.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5255 / 704-821-7643. 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.