

PRODUCT INFORMATION



LIQUID WRENCH®
PENETRATING OIL
(AEROSOL)

CODE: L106, 12

PAGE: 1 of 1

DATE: 1/24/2008

FUNCTION AND APPLICATION: A point-of-use penetrant for use by mechanics and do-it-yourselfers for disassembly of corroded pipe joints, rusted bolts and machinery, painted or gummed up metal mechanisms. Also used to clean typewriters, guns, and sports equipment.

OUTSTANDING PROPERTIES: A versatile, multi-use penetrant.

USE DIRECTIONS: Spray or squirt product on frozen joint or part. Tap the joint to set up vibrations. If part is stubborn, repeat application and allow to soak into joint for a few minutes.

PRODUCT LIMITATIONS: Does not furnish long-term lubrication or oil film protection.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8008-20-6), Naphthenic Petroleum Distillate (CAS# 64742-25-5), & Carbon Dioxide (CAS# 124-38-9) Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Vapor Harmful. Contents under pressure. **FIRST AID:** If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact, flush with water for at least 15 minutes while lifting eyelid and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation develops, get prompt medical attention. If inhaled, move to fresh air. If breathing becomes difficult get prompt medical attention.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C. Do not puncture, crush or incinerate (burn) can. Wash thoroughly after handling. **FIRE:** Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Do not use in confined spaces, enclosed garages, basements or low lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can from contact with electrical current or connections such as battery terminals because burn through may occur. Explosion or flash fire from vapors may cause serious injury or death. **CONTACT:** Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well ventilated area. Open doors and windows to prevent build up. See M. S. D. S. for more information.

Warning: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: 11 and 6 oz wt. aerosol containers.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.