

PRODUCT INFORMATION



LIQUID WRENCH®
SUPER PENETRANT

CODE: L134, 40, 49

PAGE: 1 of 1

DATE: 1/23/2008

FUNCTION AND APPLICATION: A point-of-use penetrant for use by mechanics and do-it-yourselfers for disassembly of corroded pipe joints, rusted bolts and machinery, painted or gummed up metal mechanisms. Also used to clean typewriters, guns, and sports equipment.

OUTSTANDING PROPERTIES: A versatile, multi-use penetrant.

USE DIRECTIONS: Spray or squirt product on frozen joint or part. Tap the joint to set up vibrations. If part is stubborn, repeat application and allow to soak into joint for a few minutes.

PRODUCT LIMITATIONS: Does not furnish long-term lubrication or oil film protection.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8008-20-6) & Petroleum naphthenic oil (CAS# 64742-52-5) and a Heavy paraffinic oil (CAS# 64741-88-4). Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant.

FIRST AID: If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. If eye contacted, flush with water for at least 15 minutes and get prompt medical attention. If skin is contacted, wash thoroughly with soap and water. If irritation develops, get prompt medical attention. If inhaled, move to fresh air. If breathing is difficult, get prompt medical attention.

STORAGE & HANDLING: Store in a dry, well-ventilated area below 120°F/49°C. away from ignition sources and oxidizers. **DANGER: FIRE:** Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Do not use in confined spaces, enclosed garages, basements or low-lying areas where vapors can collect.

CONTACT: Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. For long term exposure, wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe mist. Use only in well-ventilated area. Open doors and windows to prevent build up. See M. S. D. S. for more information.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: One gallon plastic bottle, 5 gallon pail and 54 gallon drum.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5255 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.