

PRODUCT INFORMATION



LIQUID WRENCH® NON FLAMMABLE LUBRICATING & Penetrating Oil with Cerflon

CODE: L312

PAGE: 1 of 1

DATE: 1/23/2008

FUNCTION AND APPLICATION: **LIQUID WRENCH® SUPER LUBRICANT with Cerflon** lubricates and protects surfaces. Fast penetrating solvents free rusted and frozen bolts and parts. Rust inhibitor protects metal parts from corrosion. **Cerflon** increases lubricity.

USE DIRECTIONS: Shake well before using. Spray lightly on frozen or corroded parts. Tap to set up vibration to help fast penetration and free parts. For difficult jobs allow to soak for 15 minutes.

PRECAUTIONS: Contains perchloroethylene (CAS# 127-18-4), Napthenic petroleum oil mixture (CAS# 64742-52-5), polytetrafluoroethylene (CAS# 9002-84-0) Carbon Dioxide propellant (CAS# 124-38-9). Harmful if Swallowed. Eye and Skin Irritant. Vapor Harmful. Contents under pressure.

FIRST AID: If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact, flush with water for at least 15 minutes which lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If inhaled, move to fresh air. If breathing becomes difficult, get prompt medical attention. See M. S. D. S. for more information.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C. Do not puncture, crush or incinerate (burn) can. Wash thoroughly after handling. Do not use in confined spaces, enclosed garages, basements or low-lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can from contact with electrical current or connections such as battery terminals because burn through may occur.

CONTACT: Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well ventilated area. Open doors and windows to prevent build up. **KEEP AWAY FROM CHILDREN AND ANIMALS.**

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

WARNING: This product contains a chemical known to the State of California to cause cancer.

CONTAINER DESCRIPTION: This product is available in 11 oz (311g) aerosol can.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.