

PRODUCT INFORMATION



INDUSTRIAL CHAIN LUBE WITH MOLY AEROSOL

CODE: L716

PAGE: 1 of 1

DATE: 1/23/2008

FUNCTION AND APPLICATION: A superior lubricant formulated for chains, cables and wherever extreme pressure/temperature occur. Can easily be applied by spraying on surfaces. INDUSTRIAL CHAIN LUBE (WITH MOLY) contains small particles of molybdenum disulfide (MOLY) which provide reduced friction lubrication.

OUTSTANDING PROPERTIES: An extreme pressure lubricant with anti-sling components for adherence at high RPM's. Can be used with servo mechanisms, flexible drives, control linkages, automatic vending machines, office equipment, hinges, drawer slides, chair swivels, printing machinery as well as many other applications. It can also be used in transportation applications such as clutch cables, brake pedals, pivot points, springs, throttle linkages, hood/trunk hinges, locks, latches, hand brake cables, manual transmission linkages, adjustable seat runners/latches, front/rear springs, door/window mechanisms, jacks/jack stands. Also used in mechanical handling equipment in pivots, control cables, conveyors, rails, rollers, overhead cranes, lifts, gate locks, gate slide cables, hoists, pulleys, pulley blocks, winches, transfer equipment, cams, slides and plungers. For agricultural and off-road equipment, tractors, hitch points, pivots, chains, sprockets, shafts, cams, etc. Can be used at every point not provided with grease nipples, filler caps or plugs.

USE DIRECTIONS: For best results, contents should be above 60°F. 1. SHAKE WELL before using. During use, shake for about 10 seconds every 2 to 3 minutes. 2. Use extension tube for pin-point application and hard to reach areas.

PRODUCT LIMITATIONS: Avoid use on rubber tile, asphalt, black-top, plastic or other surfaces

which may be damaged by petroleum solvents.

PRECAUTIONS: Contains (CAS#) Tetrachloroethylene (127-18-4), Petroleum process oil (64742-25-5), Heavy paraffinic (64741-88-4), Petroleum base oil (64742-18-3) and Carbon Dioxide (124-38-9). Eye and skin irritant. Vapor harmful. Harmful or fatal if swallowed. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. If irritation persists, get prompt medical attention. If inhaled, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention. If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately.

STORAGE & HANDLING: Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Exposure to high temperatures may cause bursting. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. The wearing of contact lenses while working with this product is in advisable. Keep away from children and animals.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: Aerosol, Net wt. 15 oz.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5255 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.