

PRODUCT INFORMATION



LIQUID WRENCH
ANTI-SEIZE LUBE

CODE: L808

PAGE: 1 of 1

DATE: 1/29/2008

FUNCTION AND APPLICATION: Anti-Seize Lube prevents corrosion, seizing and galling of joints, gaskets and unions. This material can be used for extreme temperature and pressure ranges. This product is designed for use as: a thread lubricant, pipe joint compound, valve stem lubricant, and a gasket sealer.

OUTSTANDING PROPERTIES: This product meets Mil-A-907E specifications for Anti-Seize lubricants. Permits ease of assembly and disassembly. It will not wash away. Anti-Seize Lube forms a thin anti-corrosive film that lubricates and has good anti-wear resistance. Anti-Seize Lube prevents metal surfaces from bonding together from the combined effects of high temperature and corrosive atmospheres.

USE DIRECTIONS: Thread **lubricant:** Apply to threads prior to assembly. A small amount will protect against rust and corrosion, and will allow ease of disassembly. **Pipe Joint Compound:** apply to threads or flanges. Permits easy assembly and seals against leakage. **Valve Stems:** Apply as a lubricant or packing. Unaffected by water or steam at high and low temperatures. **Gasket Seals:** Apply to new gaskets: automotive engines and mufflers, boilers, piping and pumps. Etc. Withstands extreme pressures and temperatures. **Any Matting Surface:** Apply liberally to prevent fretting corrosion and to protect surfaces. May be used on rubber, plastics, glass, ceramics, metals, and most combinations of materials. **Note:** Anti-Seize Lube is not a high-speed lubricant.

PRECAUTIONS: Contains Petroleum Oil (CAS# 64742-65-0), Metallic Copper (CAS# 7440-50-8), Aluminum (CAS# 7429-90-5), and Graphite (CAS# 7782-42-5). May be skin and eye irritant to sensitive persons. **FIRST AID:** For eye contact, flush eye for 15 minutes while lifting eyelids and get prompt medical attention. Do not rub eyes as metallic component could scratch cornea. For skin contact, wash with soap and water. If swallowed do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For Inhalation, move person to fresh air.

STORAGE & HANDLING: Store in a cool place below 100°F, away from acids, ignition sources and oxidizing agents. Use with adequate ventilation. Keep lid tightly closed when not in use. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: This product is available in an 8-oz. (226 g) bottle.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.