

# PRODUCT INFORMATION



## UNIVERSAL POWER STEERING FLUID WITH STOP LEAK

### CODE

M2713, 32, 34,  
40

PAGE 1 of 1

DATE 03/19/2008

**FUNCTION AND APPLICATION:** A top off power steering fluid with stop leak is designed for vehicles requiring a specific type of non synthetic fluid for proper operation of power steering systems. Meets service requirements of GM, Ford, and Chrysler.

**OUTSTANDING PROPERTIES:** A non-corrosive top off fluid that works in all non synthetic power steering systems to keep power steering fluids at proper levels. Helps prevent leaks by protecting seals and hoses. Power Steering Fluid is formulated with detergent additives for a cleaner system and anti-foaming agents. Intermixes with factory fluids, making steering easier and smoother. Meets service requirements of GM, Ford, and Chrysler.

**USE DIRECTIONS:** With motor off, add to power steering system to maintain level. Check regularly and replenish as needed.

**PRODUCT LIMITATIONS:** Not an OEM fluid. Not to be used with synthetic power steering fluids.

**PRECAUTIONS:** Contains Petroleum Oil (CAS# 64742-52-5), Aromatic petroleum distillate (64742-95-6), Chlorinated paraffin (63449-39-8) and Zinc Thiophosphate Derivative (proprietary). DO NOT TAKE INTERNALLY. Mild eye and skin irritant. Contains traces of dithiophosphate derivative, which may have adverse reproductive effects. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. If inhaled, move to fresh air. If breathing becomes difficult, get prompt medical attention. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and launder before re-use. Consult a physician if irritation persist.

**STORAGE & HANDLING:** Store in a cool place below 120°F away from acids, ignition sources and oxidizing agents. KEEP AWAY FROM CHILDREN AND ANIMALS.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** Packaged in 12, 32 fl. oz and 1 gallon plastic containers, and in a 5-gallon metal container.

**SPECIAL NOTATIONS:** Consult owners manual for proper use of all additives.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC / 704-821-7643. 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.