

# PRODUCT INFORMATION



## FUEL INJECTION AIR INTAKE CLEANER

**CODE:** M4712

**PAGE:** 1 of 1

**DATE:** May 2008

**FUNCTION AND APPLICATION:** FUEL INJECTION AIR-INTAKE CLEANER is formulated scientifically for modern fuel injected engines. This product is needed to maintain the efficient operation of the air intake components; throttle valve body, butterfly and idle intake control valves. Deposits hamper the smooth function of the air intake system, causing hard starting, rough idling, and poor running. Use of FUEL INJECTION AIR-INTAKE CLEANER eliminates these problems.

**USE DIRECTIONS:** Use every 3 months or 3,000 miles. Engine should be off and cool. Disconnect air intake boot at the engine side. Place absorbent cloth or toweling to absorb excess product which will drain from the air cleaner during use. Spray liberally into throat, while moving the butterfly valve open and closed. Use of the entire can is recommended. Replace air intake hose assembly and drive vehicle immediately. Safe for catalytic converters and oxygen sensors. **NOTE: If cleaner is accidentally sprayed on painted surfaces, rinse off with water immediately to avoid paint removal.**

**PRECAUTIONS:** Contains (CAS#) Xylene (1330-20-7), Toluene (108-88-3), Methanol (67-56-1), Acetone (67-64-1), Heavily hydrotreated petroleum distillate (64742-54-7) and Propane Propellant (74-98-6), Extremely flammable. Failure to follow specific instructions could cause flash fires resulting in bodily injury and even death. **CANNOT BE MADE NON-POISONOUS. FIRST AID:** If swallowed, **DO NOT INDUCE VOMITING.** Call the Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash with soap and water. If irritation persists get prompt medical attention. For Inhalation, remove to fresh air. If breathing becomes difficult, get prompt medical attention.

**STORAGE AND HANDLING:** Store in a cool, dry, well ventilated area. Do not puncture or incinerate container. Do not expose to heat, sparks, open flames or temperatures above 120 F. Do not place on radiator, stove or in direct sunlight. Keep from contact with electrical connections such as battery terminals. Avoid prolonged contact with skin and breathing vapor or spray mist. Use only with adequate ventilation Do not use in confined spaces such as garages, engine compartments of boats and vans where vapors may collect and ignite in a flash fire. Adequate ventilation must be maintained under all circumstances. **NOTE.** Not for diesel engine use. Read entire label before using this product! **KEEP AWAY FROM CHILDREN!**

**DISPOSAL:** Use and dispose of product, container and residue in accordance with all local, state and federal laws and regulations. Damaged container should be disposed of because of the potential for exposure to its fumes, vapors and other hazards.

**CONTAINER DESCRIPTION:** This product is available in 12 oz aerosol can.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.