

# PRODUCT INFORMATION



## OCTANE PERFORMANCE BOOSTER

CODE: M5112

PAGE: 1 of 1

DATE: 4/10/2008

**FUNCTION AND APPLICATION:** Restores engine performance. Reduces knock, ping and hesitation. Cleans injectors, intake valve, and combustion chamber deposits. Use as needed.

**OUTSTANDING PROPERTIES:** Removes deposits which tend to cause engine's octane requirements to rise. After use of product, many engines will accept the regular unleaded gasoline's more readily without knocking, pinging and after-run. Octane Performance Booster is an efficient product for cleaning up the fuel system. Restores spray pattern to that of new injectors allowing more efficient engine operation. Contains additives that remove water and fights rust. Reduces emissions.

**USE DIRECTIONS:** Use as needed. Add to fuel tank at fill up. Run engine normally until fuel tank nearly empty. (Do not fill up with fuel until tank nearly empty.)

**PRODUCT LIMITATIONS:** For vehicles with severe deposits, a second treatment may be necessary to alleviate deposits.

**PRECAUTIONS:** Contains Aliphatic Hydrocarbon Petroleum Distillate (CAS# 68476-34-6). Harmful or fatal if swallowed. Eye and skin irritant. Vapor harmful. **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING! Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. Remove contaminated clothing and launder before re-use. If inhaled, move to fresh air immediately. If breathing becomes difficult, get prompt medical attention.

**STORAGE & HANDLING:** Store in a cool place below 120°F away from acids, ignition sources and oxidizing agents. Combustible. Keep away from fire, heat or sparks. Use only with adequate ventilation. Wearing contact lenses while working with this product is inadvisable. Keep away from children and animals.

**DISPOSAL:** Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

**CONTAINER DESCRIPTION:** Packaged in 12 fluid ounce plastic bottles.

## Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.