

PRODUCT INFORMATION



BRAKE CLEANER (AEROSOL)

CODE: M720

PAGE: 1 of 1

DATE: May 2008

FUNCTION AND APPLICATION: A fast-acting, deep-cleaning formula that the professionals know, and trust!. Quickly removes brake dust without leaving a residue behind. The proper use of SOLDER SEAL® GUNK® BRAKE CLEANER can help improve performance. Its high solvency and fast evaporation quickly dissolves and flushes away brake fluid, oil, grease and other contaminants from all types of brake and C.V. joint assemblies. It cleans instantly and can be applied without disassembling the brake unit. It leaves no residue and helps stop disc brakes squeal and "chatter". Use SOLDER SEAL® GUNK® BRAKE CLEANER on: conventional brake units, linings and shoes, drums, cylinders, springs, disc brake units C.V. joints, caliper units, brake pads, discs, and related parts.

OUTSTANDING PROPERTIES: Contains no silicones or carbon tetrachloride.

USE DIRECTIONS: Brake pads or linings that have been heavily soiled (impregnated) with oil or grease should be replaced, not cleaned. Consult a professional mechanic. To help retard the release of asbestos dust and other airborne particulate matter, follow these DIRECTIONS FOR USE carefully and in numerical order:

- 1) Protect rubber parts and boots from accidental overspray.
- 2) 2) Lightly wet down surfaces to be cleaned by spraying in short bursts from a distance of 18 to 24 inches. DO NOT SPRAY ON HOT METAL SURFACES LIKE EXHAUST PIPES.

- 3) After surfaces have been wetted, continue spraying at a distance of 12 to 18 inches to flush contaminants from surfaces. Spray brake parts thoroughly, then allow to air dry or wipe with soft clean cloth. If deposits are heavy, repeat application. Collect any runoff for proper disposal. See DISPOSAL, below.

PRODUCT LIMITATIONS: THIS PRODUCT WILL ATTACK PAINTED SURFACES AND PLASTIC. IF SPRAYED ON, DO NOT RUB SURFACES, FLUSH WITH WATER IMMEDIATELY.

PRECAUTIONS: Contains Perchloroethylene (CAS# 127-18-4) and carbon dioxide(124-38-9). Contents under pressure. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently and cause serious injury. Do not breathe asbestos, dust particles, or vapors. Use only in a well-ventilated area, open doors and windows to prevent vapor build up. NIOSH approved respirator recommended; may be required for professional users; consult MSDS for exposure limits. Mechanical ventilation may be necessary to prevent a hazardous concentration of vapors if more than one container is used in less than a 15-minute period. **INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE, CAN CAUSE PERMANENT ORGAN DAMAGE OR CAN BE FATAL.** Avoid contact with eyes, skin or clothing. Remove contaminated clothing and wash before reuse. Remove contact lenses before use. Skin absorption through prolonged or repeated contact can result in organ damage. Wear chemical goggles and solvent proof gloves and apron. Wash

thoroughly after handling. This product is non-flammable. Do not use in confined spaces such as basements, engine compartments of boats and vans where vapors may collect. Adequate ventilation must be maintained under all circumstances.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID: For EYE contact: Flush thoroughly with water for 15 minutes lifting upper and lower eyelids occasionally and get prompt medical attention. For SKIN contact: Wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If INHALED, remove to fresh air. If breathing becomes difficult, get prompt medical attention. IF SWALLOWED DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room immediately. Aspiration of vomitus into lungs can cause chemical pneumonitis, which can be

fatal. Never give anything by mouth to an unconscious person.

STORAGE AND HANDLING: Store in a cool, dry, well ventilated area. Do not puncture, crush or incinerate (burn) can. KEEP AWAY FROM CHILDREN AND ANIMALS.

DISPOSAL: Disposal of product runoff in water courses, sewers, or on the ground is prohibited. Proper disposal includes collecting and recycling. Always use and dispose of product, container, and residue in accordance with all local, state and federal laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: This product is available in 19 OZ (538 g) aerosol container.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.