

PRODUCT INFORMATION



SQUEAL MEDIC

CODE: M725, M72502

PAGE: 1 of 1

DATE: May 2008

FUNCTION AND APPLICATION: Squeal Medic is a brake finishing treatment designed to eliminate brake noise when applied to drums or rotors. Squeal Medic does not change the pedal feel or modify the break-in properties of the linings and prevents oxidation of drums and rotors. Squeal Medic does not affect braking performance.

OUTSTANDING PROPERTIES: Squeal Medic is effective on all vehicle braking systems, requires no drying time, and can be used as an anti-seize lubricant on lug nuts. When applied to the drums and rotors, Squeal Medic fills voids to help eliminate break squeal and harmonic vibration resulting from uneven surfaces. Use on new or existing systems. Safety tested by an independent laboratory to ensure safe braking after use. Does not decrease braking effectiveness or lessen coefficient of friction when used as directed.

USE DIRECTIONS. FOR PROFESSIONAL USE ONLY.

1. Shake can well before using.
2. Use on a clean system.
3. Before assembling the unit, spray a light coat (2 seconds) directly onto the rotor or drum surface. Use sparingly. Then assemble the unit.
4. After assembling the unit, drive the vehicle applying the brakes 5-8 times while driving at low speed.

PRODUCT LIMITATIONS: This product will attack painted surfaces and plastic. If sprayed on, do not rub surfaces, flush with water immediately.

PRECAUTIONS: DANGER. Contains liquified petroleum gas (68476-86-8), stoddard solvent (CAS# 8052-41-3), hydrotreated light distillate (CAS# 64742-47-8), hexane (CAS#110-54-3) and metal flake (CAS# 7429-90-5). Extremely Flammable. Use in a well-ventilated area away from heat, sparks, or open flame. Ensure adequate ventilation especially in confined spaces such as enclosed garages or other low-lying areas where vapors can collect. Contents

under pressure. Do not puncture or incinerate container. Do not expose to heat, direct sunlight, or store at temperatures above 120°F.

FIRST AID: Eyes: Flush thoroughly with water for 15 minutes lifting upper and lower eyelids and get prompt medical attention. **Skin:** Wash thoroughly with soap and water. If irritation develops, get prompt medical attention. **Inhalation:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **Ingestion:** DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately

STORAGE AND HANDLING: Store in a cool, dry, well ventilated area below 120°F. Do not puncture, crush or incinerate can. KEEP AWAY FROM CHILDREN AND ANIMALS.

DISPOSAL: Disposal of product runoff in water courses, sewers, or on the ground is prohibited. Proper disposal includes collecting and recycling. Always use and dispose of product, container, and residue in accordance with all local, state and federal laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: This product is available in 2 and 11.25 oz aerosol container.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643. 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.