

PRODUCT INFORMATION



SOLDER SEAL/GUNK ADVANCED FORMULA DIESEL SYSTEM PURGE

CODE: M8132ER

PAGE: 1 of 1

DATE: 4/13/2009

FUNCTION AND APPLICATION: The liquid **Diesel System Purge** is intended for cleaning diesel fuel injection systems, specifically while the engine is in operation. The purge is equally effective in all brands of electric and portable pneumatic devices used for the purpose of fuel injector cleaning, as well as in cleaning stations of RCP type. The product effectively removes impurities from the fuel system, restores engine output and the optimal cone of fuel spray from the injectors. Proper use produces an improvement in vehicle performance and a decrease in fuel consumption. The liquid "Diesel System Purge produces an exceptional unclogging effect, breaking apart accumulation and removing any buildup on the intake valves, the pistons, and in the combustion chambers. It acts to balance compression in the cylinders as well as to decrease the toxicity and CO contents of the exhaust gases. The purge is safe for catalytic converters. The purge has been proven to cause no negative effects on glow plug performance, or on any rubber or plastic components of the fuel system.

USE DIRECTIONS: Use Diesel System Purge with an injector cleaning apparatus. Follow instructions provided on the label. Professional users must read the Material Safety Data Sheet (MSDS) before using this product. MSDS's are available upon request by calling 704-821-7643 or visit www.gunk.com.

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. Do not smoke while using this product. Contains (CAS#) Petroleum Based Oil (8008-20-6), Diacetone Alcohol (123-42-2), 2-Ethylhexyl Nitrate (27247-96-7) and detergent/dispersant blend (Proprietary). **FIRST AID:** If swallowed, DO NOT INDUCE VOMITING. Get medical help immediately. For eye contact, flush thoroughly with water for 15 minutes while lifting eyelids. For skin contact, wash with soap and water. If irritation persists, get prompt medical attention.

STORAGE AND HANDLING: Use with adequate ventilation away from heat, spark, and flames. Avoid inhaling vapors and wash after handling. Store below 49°C. KEEP AWAY FROM CHILDREN.

DISPOSAL: Use and dispose of product, container and residue in accordance with all laws and regulations. Emptied containers contain product residue or vapors so follow all warnings even after container is emptied. .

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, 28079-5225 / 704-821-7643

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.