

PRODUCT INFORMATION



CYCLE CHAIN LUBE

CODE: ML2S

PAGE: 1 of 1

DATE: June 2008

FUNCTION AND APPLICATION: Lubricates and quiets chain noise. Cleans and protects all types of open chains and flexible cables. Safe for O-rings.

OUTSTANDING PROPERTIES: No chlorinated solvents. Clings; Contains special anti-silting and anti-wear additives. Protects against oxidation. Adds to sprocket and chain life.

USE DIRECTIONS: For best results, clean chain with SOLDER SEAL® GUNK® Liquid Wrench® Super Lubricant to remove road grime, grit and sand. Insert extension tube in valve button. Apply CYCLE CHAIN LUBE immediately after cleaning along full length of chain. Run chain slowly to insure complete coverage and penetration. Reapply as needed.

PRODUCT LIMITATIONS: Avoid use on rubber tile, asphalt, black top, plastic or other surfaces deleteriously affected by petroleum solvents.

PRECAUTIONS: Contains (CAS#) Aliphatic Petroleum Distillates (8052-41-3), Naphthenic Oil (64742-52-5), Ethylene-Propylene Copolymers (CAS# Mixture) and Carbon Dioxide (CAS# 124-38-9).

Flammable. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Vapor Harmful. **FIRST AID:** If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room Immediately. If eye contacted, flush with water for at least 15 minutes while raising eyelids and get prompt medical attention. If skin is contacted, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If inhaled, remove to fresh air. If breathing becomes difficult get prompt medical attention. See Material Safety Data Sheet for more information.

STORAGE & HANDLING: Store in a dry, well ventilated area below 120°F/49°C. Do not puncture, crush or incinerate container. Wash thoroughly after handling.

FIRE: Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Do not use in confined spaces, enclosed garages, basements or low lying areas where vapors can collect. Do not place can on hot surfaces or in direct sunlight which could cause can to burst violently. Keep can from contact with electrical current or connections such as battery terminals because burn through may occur. Explosion or flash fire from vapors may cause serious injury or death. **CONTACT:** Avoid contact with eyes, skin or clothing. remove contaminated clothing and wash before reuse. Remove contact lenses before use. Wear chemical goggles and solvent-proof gloves and apron. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well ventilated area. Open doors and windows to prevent build up. **INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE, CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE OR CAN BE FATAL.** Keep away from children.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: Packaged in 12 oz (340 g) net wt aerosol can.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.