

PRODUCT INFORMATION



Super-Concentrated Fuel System Treatment

CODE: MSUV16

PAGE: 1 of 1

DATE: May 2008

FUNCTION AND APPLICATION: Solder Seal®/Gunk® Super Concentrated Fuel System Treatment is specifically designed to clean fuel systems in gasoline-powered vehicles with large gas tanks up to 45 gallons in capacity. Solder Seal®/Gunk® Super Concentrated Fuel System Treatment will: cleanup injectors, intake valves, pistons and combustion chambers, restore acceleration and lost power, reduce stalling and smoothes rough idle, and helps reduce exhaust emissions.

OUTSTANDING PROPERTIES: Deposits that form in your fuel system and engine can decrease fuel economy, increase emissions and cause poor idle, power loss, hesitation, knocking and pinging. These deposits cause the automatic knock sensor in your engine to change the ignition timing, 'de-tuning' the engine and reducing performance and fuel economy. The synthetic polyetheramine technology in Solder Seal®/Gunk® Super Concentrated Fuel System Treatment provides one-tank cleanup of fuel injectors, carburetors, intake valves, and combustion chambers. This product will not harm oxygen sensors, catalytic converters, or other emissions equipment. Can be used with all gasoline: oxygenated, reformulated, or unleaded.

USE DIRECTIONS: One pint (16 fl.oz.) bottle treats up to 45 gallons of gasoline. Add the entire contents of the bottle to the gasoline tank, then fill tank. For best results, do not refill tank again until nearly empty.

DANGER: Contains petroleum distillates (CAS# 8008-20.6) and polyetheramine detergent blend (proprietary). Harmful or fatal if swallowed. Eye and Skin Irritant. Combustible, Vapor Harmful.

FIRST AID: **Eyes:** Flush thoroughly with water for 15 minutes lifting upper and lower eyelids and get prompt medical attention. **Skin:** Wash thoroughly with soap and water. If irritation develops, get prompt medical attention. **Inhalation:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **Ingestion:** DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately

STORAGE AND HANDLING: Store in a cool, dry, well ventilated area below 120°F. Keep away from heat and flame. Use with proper ventilation. **INHALING CONCENTRATED VAPORS INTENTIONALLY OR OTHERWISE CAN BE HARMFUL OR FATAL. KEEP AWAY FROM CHILDREN AND ANIMALS.** Warning: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm.

DISPOSAL: Use and dispose of product, container, and residue in accordance with all local, state and federal laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION This product is available in a 16 fl.oz. (1 Pt) plastic container.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC, 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.