

PRODUCT INFORMATION



**TITE-SEAL®
GASKET & JOINT SEALING COMPOUND
LIGHT WEIGHT**

CODE: T2066, T2075

PAGE: 1 of 1

DATE: May 2008

FUNCTION AND APPLICATION: TITE-SEAL® LIGHT WEIGHT is a flexible compound for use as a joint sealing compound, caulking compound, corrosion preventative, lubricant, threaded joint dressing insulating material or filler with packing. Used on head and manifold gaskets of automotive and aircraft engines, water heater fittings and gaskets, gas range valves and fittings, pipe threads on dry-cleaning solvent filters, railroad and truck air-brakes, fittings and lines, etc. For all metal-to-metal unions with any kind of gasket.

OUTSTANDING PROPERTIES: TITE-SEAL® LIGHT WEIGHT is unaffected by water, oil, gasoline, glycerin, steam, gas vapor, exhaust fumes and most hard-to-hold liquids. Withstands extreme temperatures; will not harden, making connections, vibration-proof and easy to disassemble for repairs and adjustments. Prevents corrosion and "freezing" of metal parts. Expands and contracts with temperature changes without affecting seal.

USE DIRECTIONS: TITE-SEAL® LIGHT WEIGHT will form seals at temperature range 20 F to 250 F. Before applying wipe surfaces dry and clean. Then simply spread on. With gaskets: Coat joint surfaces, spreading evenly. Without gaskets: Coat joint surfaces and embed small thread or string as binder. As a filler: Apply as a bond between regular packing and metal surfaces. Do not use a thinner.

PRECAUTIONS: Contains a mixture of vegetable oils and clays. May be skin and eye irritant to sensitive persons. Harmful if swallowed. **FIRST AID:** In case of contact, wash skin with soap and water. For eye contact, flush promptly with water for at least 15 minutes and get prompt medical attention. If ingested, do not induce vomiting. Call Poison Control Center, Physician, or Hospital Emergency Room immediately.

STORAGE & HANDLING: Store in a cool place below 120°F away from acids, ignition sources and oxidizing agents. Keep lid tightly closed. Wearing contact lenses while working with this product is inadvisable. Keep away from children.

DISPOSAL: Dispose of container, residue, and excess product in accordance with all federal, state, and local laws and regulations.

CONTAINER DESCRIPTION: This product is available in 1 lb, 5 lb and 55 lb can sizes.

Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, NC 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: WHILE THIS INFORMATION IS PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, RADIATOR SPECIALTY COMPANY DOES NOT GUARANTEE SATISFACTORY RESULTS FROM RELIANCE THEREON. THE DATA IS OFFERED SOLELY FOR YOUR INFORMATION AND RADIATOR SPECIALTY COMPANY DISCLAIMS ALL LIABILITY FOR ANY LOSS OR DAMAGE FROM ITS USE. THOROUGHLY TEST ANY APPLICATION ACCORDING TO THE PRODUCT DIRECTIONS AND INDEPENDENTLY CONCLUDE SATISFACTORY PERFORMANCE. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE THE PRODUCT IN VIOLATION OF ANY PATENT.